



### Wire Harness Tape – Hand-tearable Cloth Tape

#### HelaTape Protect 180



HelaTape Protect 180 is very flexible and used for cable harnessing.

#### Features and benefits

- High quality Polyester Fabric harnessing tape
- Rubber-based adhesive offers very good heat and media resistance
- High temperature stability from -40 °C to +125 °C
- Temperature resistance tested according to LV312
- Very good resistance against abrasion
- Material is very flexible and tearable by hand
- Provides long term reliability under varying and extreme environmental conditions
- Excellent ageing resistance, stable against rotting

<b>MATERIAL</b>	Polyester (PET)
<b>Operating Temperature</b>	-40 °C to +125 °C
<b>Adhesion to Steel</b>	3 N/10 mm
<b>Adhesion to Backing</b>	3 N/10 mm
<b>Elongation at break</b>	15 %
<b>Breaking Strength</b>	65 N/10 mm



### Wire Harness Tape – Strong, High Temperature Cloth Tape

#### HelaTape Protect 250



HelaTape Protect 250 is designed for cable harnessing and offers a very high temperature resistance.

#### Features and benefits

- High temperature Polyester Fabric harnessing tape
- Special acrylate-based adhesive offers very good heat and media resistance
- Very high temperature stability from -40 °C to +150 °C
- Temperature and humidity resistance tested according to LV312
- Very good resistance against abrasion
- Material is very flexible and easy to handle
- Excellent ageing resistance, stable against rotting

<b>MATERIAL</b>	Polyester (PET)
<b>Operating Temperature</b>	-40 °C to +150 °C
<b>Adhesion to Steel</b>	2.5 N/10 mm
<b>Adhesion to Backing</b>	2 N/10 mm
<b>Elongation at break</b>	15 %
<b>Breaking Strength</b>	180 N/10 mm



#### HelaTape Protect 180

TYPE	Thickness (T)	Width (W)	Length (L)	Colour	Article-No.
HATAPE-PROTECT180	0.18	19.0	25.0 m	Black (BK)	712-10002

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.

#### HelaTape Protect 250

TYPE	Thickness (T)	Width (W)	Length (L)	Colour	Article-No.
HATAPE-PROTECT250	0.25	19.0	25.0 m	Black (BK)	712-10003

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.