

TELAIO	
COLLARINO	
FORCELLA	Alloy, 38.6
TELAIO	RockShox 35 Silver, 35mm stanchion, Turnkey damper, S1: 150mm travel, S2-S6: 160mm travel
SOSPENSIONI AMMORTIZZATORE	Specialized M5 premium alloy, BB height adjust, S-Sizing, internal cable routing, 150mm travel, 148mm spacing
COCKPIT ATTACCO	RockShox Deluxe Select R, rebound adjust, S1: 52.5x210mm, S2-S6: 55x210mm
SELLA	Alloy Trail Stem, 35mm bar bore
NASTRO	Body Geometry Bridge Saddle, steel rails
MANUBRIO	Specialized Trail Grips
REGGISELLA	Alloy, 35mm diameter, 780mm width, 8-degree backsweep, 6-degree upsweep
FRENI FRENO POST.	TranzX dropper, 34.9mm, S1: 100mm, S2: 125mm, S3: 150mm. S4-S5: 170mm, S6-200mm
FRENO ANT.	SRAM Guide RE, 200mm
TRASMISSIONE GUARNITURA	SRAM Guide RE, S1-S3: 200mm, S4-S6: 220mm
CASSETTA	Praxis forged M30, custom offset, 160mm
CATENA	SRAM NX Eagle, 12-speed, 11-50t
COMANDI	SRAM NX Eagle, 12-speed
CAMBIO POST.	SRAM SL SX Eagle, 12-speed
INGRANAGGI	SRAM SX Eagle, 12-speed

RUOTE MOZZO POST.	SRAM X-Sync Eagle, 104 BCD, 32T, steel
PNEUMATICO ANT.	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
RAGGI	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
PNEUMATICO POST.	DT Swiss Industry
CERCHI	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
MOZZO ANT.	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
CAMERE	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
E-BIKE CABLAGGIO	Standard, Presta Valve
CARICATORE	Custom Specialized wiring harness
UI/REMOTE	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
MOTORE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
ELETTRONICA BATTERIA	Specialized Turbo Full Power System 2.2 Motor
	Specialized M3-500, Integrated battery, 500Wh