



## E2E-X8B1T18-M1

Sensore di prossimità induttivo, nichel-ottone, corpo corto, M18, schermato, 8 mm, CC, 3 fili, PNP NA, IO-Link COM3, connettore M12

# Specifiche

Size	M18
Mounting type	Quasi-flush
Sensing distance	8 mm
Overall length	53 mm
Thread length	34 mm
Material housing	Brass, nickel plated
Output type	IO-Link, PNP
Operation mode	NO
Connection method	Connector M12
Cable specifications	-
IO-Link function	✓
IO-Link baud rate	COM3 (230.4 kbps)
Degree of protection (IP)	IP67/IP69K

# Accessori



Y92E-J18S30

Manicotti di montaggio e-jig per sensori di prossimità M18



## Connettori e set di cavi M12

Connettori e set di cavi industriali per qualsiasi applicazione

## Area di download

Libreria CAD



### E2E NEXT

Catalogo tecnico

EN PDF 34,4 MB



### E2E(Q) - Basic Models

Elenco indice

EN PDF 719 KB



### E2E(Q) - Premium Models

Elenco indice

EN PDF 719 KB



### E2E[Q]-XxBxxxx

File IO-Link IODD

EN ZIP 1,35 MB



### IO-Link Series

Brochure

IT PDF 4,08 MB