


Mod. S245.EU **TEKNOKOMFORT** 
 TERMOVENTILATORE PTC A COLONNA
 TOWER PTC FAN HEATER

220-240V~ 50Hz 1800W



- Termoventilatore, ventilatore, umidificatore
- Resistenza in ceramica
 - Incorpora umidificatore per un'ambiente più salubre e confortevole
 - Comandi elettronici + telecomando: ogni funzione impostata, è visualizzata sul display.
 - Stand-by/ventilazione estiva
 - Ventilazione inverno: aria calda/aria molto calda
 - Temperatura ambiente regolabile (4°-32°C solo inverno)
 - Timer 8h: interrompe il funzionamento allo scadere del tempo impostato e, se in funzionamento continuo, dopo 24h
 - Oscillazione Dx/Sx
 - Umidificatore & intensità (max130ml/h) regolabile con variatore
 - Interruttore 0/1
 - Dispositivo anti-ribaltamento
 - Serbatoio acqua 1,7l
 - Superficie riscaldata 18m²
 - Grado di protezione: IP20




- Tower fan heater, fan and humidifier
- Ceramic resistance
- Electronic control + Remote control: each selected function LED panel display shows: Stand by/fan, Hot air/very hot air, Adjustable room temperature (4°-32°C, only winter)
- 8-hour Timer: shuts off the fan when the time set runs out and, in continuous operation, after 24 hours
- Left-right oscillation switch
- Humidifier & nebulising qty (max130ml/h)
- 0/1 switch
- Tip over switch
- 1,7l. water tank
- Heating capacity: 18m²
- IP20 class protection

3 in 1

TERMOVENTILATORE - TOWER FAN HEATER
 UMIDIFICATORE A ULTRASUONI - HUMIDIFIER
 VENTILATORE - FAN



TELECOMANDO
 REMOTE CONTROL




Mod. S248 **ELLISSE** 
 TERMOVENTILATORE PTC
 A COLONNA
 TOWER PTC FAN HEATER

220-240V~ 50Hz 2000W



- Resistenza in ceramica
- Interruttore 0/1
- Comandi elettronici + Telecomando: ogni funzione impostata, è visualizzata sul display
- 2 selezioni 1200-2000W+funzione aria fredda+ funzione ECO
- Pulsante oscillante destra-sinistra
- Display LCD e LED visualizzano temperatura ambiente e funzioni selezionate
- Temperatura ambiente regolabile +5°/+30°C
- Timer 7,5h
- Dispositivo antiribaltamento
- Corpo con maniglia integrata
- Superficie riscaldata 20m²
- Grado di protezione: IP20



- Ceramic resistance
- 0/1 switch
- Electronic control + Remote control: each selected function LED
- 2 heat setting 1200-2000W + cold fan function + ECO function
- Left-right oscillation switch
- LED panel display shows room temp & each selected function
- Adjustable room temperature +5°/+30°C
- Timer 7,5hrs
- Tip over switch
- Rear handle for transportation
- Heating capacity: 20m²
- IP20 class protection



TELECOMANDO
 REMOTE CONTROL

