

Cordless Heat Gun GHG 18V-50



Flexible 18V heat gun for working on the go

The most important data

Heat-up time to 300°C	6 s
Temperature levels	2

Part Number 0 601 2A6 501

> More product information

Technical data

Technical data

Heat-up time to 300°C6 sTool dimensions (height)209 mmWeight excl. battery0.59 kgTool dimensions (length)77 mmTool dimensions (width)183 mmTemperature levels2Working temperature300 - 500°CContinuously variable temperature-Cold stage, 50°C-Specifications, use175 l/min		
Weight excl. battery0.59 kgTool dimensions (length)77 mmTool dimensions (width)183 mmTemperature levels2Working temperature300 - 500°CContinuously variable temperature control-Cold stage, 50°C-Specifications, use	Heat-up time to 300°C	6 s
Tool dimensions (length)77 mmTool dimensions (width)183 mmTemperature levels2Working temperature300 - 500°CContinuously variable temperature control-Cold stage, 50°C-Specifications, use-	Tool dimensions (height)	209 mm
Tool dimensions (width)183 mmTemperature levels2Working temperature300 - 500°CContinuously variable temperature control-Cold stage, 50°C-Specifications, use-	Weight excl. battery	0.59 kg
Temperature levels 2 Working temperature 300 - 500°C Continuously variable temperature - control - Cold stage, 50°C - Specifications, use -	Tool dimensions (length)	77 mm
Working temperature300 - 500°CContinuously variable temperature control-Cold stage, 50°C-Specifications, use-	Tool dimensions (width)	183 mm
Continuously variable temperature control - Cold stage, 50°C - Specifications, use -	Temperature levels	2
control Cold stage, 50°C Specifications, use	Working temperature	300 - 500°C
Specifications, use		-
	Cold stage, 50°C	-
Airflow 175 l/min	Specifications, use	
	Airflow	175 l/min



Advantages:

- Save time: Fast heating up to 300 °C within 6 seconds
- Portability and flexibility in every working environment
- Two temperature levels (300/500 °C) and LED light for easy operation

