



DL040

Code	Nominal lumen	W	CCT	Beam
DL040/BI	690	8	3000K	40°
DL040/NE	690	8	3000K	40°

2 ANNI DI GARANZIA • YEARS OF GUARANTEE



Proiettore LED orientabile per installazione a plafone e incasso a soffitto e a parete.

Adjustable LED projector for ceiling installation or wall and ceiling recessed installation.

Projecteur LED orientable pour installation en plafonnier ou murale.

Verstellbarer LED Strahler für Decken- und Wandinstallation.

Lumens AC LED.

Lumens AC LED.

Lumens AC LED.

Lumens AC LED.

Life time 30.000h (rendimento 70%).

Life time 30.000h (70% lumen maintenance).

Durée de vie 30.000h (rendement 70%).

Lebensdauer 30.000h (Lichtstrom 70%).

Corpo in alluminio verniciato bianco o nero lucido.

Body in lucid white or black painted aluminium.

Corps en aluminium peint blanc ou noir brillant.

Gehäuse aus weiss oder schwarz glanz lackiertem Aluminium.

Vetro temperato trasparente.

Tempered transparent glass.

Verre trempé transparent.

Gehärtetes Glas.

Alimentazione a tensione di rete 220-240V.

220-240V direct connection.

Alimentation directe 220-240V.

Spannungsversorgungsnetz 220-240V.

DL040
